(19) 世界知识产权组织 国际局

PCT

(43) 国际公布日: 2005年3月31日(31.03.2005)

(10) 国际公布号: WO 2005/028772 A1

(51) 国际分类号7:

E04C 1/00, E04B 2/08

(21) 国际申请号:

PCT/CN2004/000974

(22) 国际申请日:

2004年8月23日(23.08.2004)

(25) 申请语言:

中文

(26) 公布语言:

中文

(30) 优先权:

03159561.8 200410071514.2 2003年9月23日(23.09.2003) CN 2004年7月7日(07.07.2004) CN

- (71)(72) 发明人/申请人: 汪荣勋(WANG, Rongxun) [CN/ CN]; 中国浙江省杭州市西湖区文二路益乐新村南一 区22幢1楼, Zhejiang 310012 (CN)。
- (74) 代理人: 上海专利商标事务所(SHANGHAI PATENT & TRADEMARK LAW OFFICE); 中国上海市桂平路435号, Shanghai 200233 (CN)。
- (81) 指定国(除另有指明, 要求每一种可提供的国家保护): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW,

BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM,

DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW


(84) 指定国(除另有指明, 要求每一种可提供的地区保护): ARIPO(BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), 欧亚专利(AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), 欧洲专利(AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

本国际公布:

- 包括国际检索报告。
- 在修改权利要求的期限届满之前进行,在收到该修改后 将重新公布。
- 所引用双字母代码和其它缩写符号,请参考刊登在每期 PCT公报期刊起始的"代码及缩写符号简要说明"。

(54) Title: BLOCK FOR BUILDING WALL AND THE WALL BUILT WITH SAID BLOCKS

(54) 发明名称: 用于形成墙体的砌块及其形成的墙体



(57) Abstract: A kind of block for building wall and the wall built with said blocks. There are many analogous blocks laid to overlap and stagger with upper/nether block continuously in said wall. The block extends lengthways and comprises top surface (1), bottom surface (2) and two end surfaces (3); the cross section thereof on the whole is a converse trumpet shape; the top surface (1) has a mid ridge (4) higher than the two sides of the surface so as to form the left /right supporting slope (5); the top surface (1) and the bottom surface (2) are formed in this way: when a block overlap with a analogous block thereunder to form a wall, the left and right supporting slope (5) become a blocking structure to lock the two blocks neighbored up and down, the raised dimension of the mid ridge (4) can cut off space-time trochoid. This invention also provides the assistant blocks, which cooperate with said blocks when building wall.



(57) 摘要

一种用于形成墙体的砌块及其形成的墙体。在所述的墙体中数个类似的砌块连续的错位叠置。砌块是纵向型材,包括顶面(1)、底面(2)和两个端面(3);其横截面整体上呈朝下的喇叭口状;顶面(1)有中部脊(4),两侧低,形成左、右支承坡(5);顶面(1)和底面(2)是这样形成:当砌块与下面的类似砌块叠置形成墙体时,左、右支承坡(5)成为阻拦结构并使上下相邻砌块互相锁定,中部脊(4)的突起尺寸可以切断时空轨迹线。本发明还提供了与砌块砌筑配合的辅助砌块。